# Krytech Arm 532

#### **DESCRIPTION AND GENERAL PROPERTIES**

- Length (cm) 45cm
- · Colour/Color Grey
- Interior finish Seamless textile support from HDPE fibres
- Packaging 6 pairs/bag 72 pairs/carton
- Complementary information One size only / Tested according to the EN388 test methods



#### **PERFORMANCE RESULTS**

### Certification category 2





334X ISO 13997 : 7.6 N (731 g)

#### ISO 13997 defines the weight on the blade required to cut in a single movement.

Data was obtained according to ISO 13997, from the average of several measurements. As Individual specimens will obviously have greater or lesser cut resistance than the average, so this result can provide only a general indication of the cut resistance of any protective material.

#### Legends **MECHANICAL** LOW CHEMICAL MICRO-ORGANISMS **RADIOACTIVE** PROTECTION **HAZARDS** EN 374 CONTAMINATION EN 388 EN 421 PERFORMANCE LEVELS 0-4 0-5 0-4 Puncture resistance SPECIFIC CHEMICAL **COLD HAZARDS** Tear resistance **PROTECTION** EN 511 Blade cut resistance EN 374 PERFORMANCE LEVELS -Abrasion resistance Letter Chemical 0-4 0-4 0 or 1 Code product Water permeability Methanol Contact cold resistance AND FIRE В Acetone Convective cold resistance EN 407 Acetonitrile D Dichloromethane PERFORMANCE LEVELS Carbon Disulfide 0-4 0-4 0-4 0-4 0-4 Toluene Resistance to large quantities of molten metal G Diethylamine Tetrahydrofurane Resistance to small drops of molten metal -Radiant heat resistant Ethyl acetate Convective heat resistance n-Heptane -Contact heat resistance Sodium hydroxide 40% Sulphuric acid 96% -Burning behaviour

For more details: www.mapa-pro.com



## Krytech Arm 532

#### **DESCRIPTION AND GENERAL PROPERTIES**

- · An ultra thin thumb hole area provides better comfort and increased safety while maintaining dexterity
- Velcro Adjustable strap for secure fit
- Washable until 5 cleaning cycles (see laundering and drying conditions)

#### **MAIN FIELDS OF USE**

#### Automotive/mechanical industry

- · Assembly of thin metal sheets
- Automotive assembly
- · Handling metal parts
- Mechanical maintenance

#### Mechanical industry

#### **INSTRUCTIONS FOR USE**

#### Instructions for use

Not be used next to moving machinery.

The cuff must be worn associated with a glove with at minimum the same levels of protection.

Adjust the cuff on the arm with the Velcro® strap.

Caution: inappropriate sleeve usage or cleaning may alter performance level. For more information on sleeve usage or performances, contact your distributor or Mapa Professional Technical Customer Service (stc.mapaspontex@mapaspontex.fr)

#### Laundering conditions

Performances of the sleeves are not negatively affected by cleaning up to 5 cleaning cycles\* under the conditions described above: Use of a household or industrial washing machine and a standard liquid detergent, synthetic program temperature 60 ° C and spin drying at 400 rotations per minute. It's advisable to attach the magic tape before to put the sleeve inside the washing machine. Improper use of the gloves or submitting them to a cleaning or laundering process that is not specifically recommended can alter their performance levels. The customer or the launderer is sole responsible for the compliance with the washing conditions.

\* Test performed: 5 successive washes on unworn gloves.

#### **Drying conditions**

Tumble drying at 60°C maximum. Put the sleeves on dry and clean hands. Ensure the inside of the sleeves is dry before putting them on again.

#### **LEGISLATION**

This product is not classified hazardous according to the regulation (EC)  $n^{\circ}1272/2008$  of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation  $n^{\circ}1907/2006$  of the European Parliament and of the Council (REACH).

• Issued by the notified body nr

0075

C.T.C - 4 rue Hermann Frenkel - 69367LYON Cedex 07- France

