



model 7610

AXION MSR™ Eye/Face Wash

FEATURES & BENEFITS

SAFETY

8" x 10-3/4" (20.3 x 27.3 cm) universal emergency sign make the unit easily detected in an emergency. Test card to record weekly checks helps maintain the unit best working quality.

VALVE

Units pull-down to activate design produces a full continuous flow of water and provides an easy start to the irrigation process.

MOUNTING

Unit mounts at the back of sink so when the unit is not in use, it is as far out of the way as possible.

EYE/FACE WASH

AXION MSR™ eye/face wash head (patent pending) uses an inverted directional laminar flow to sweep contaminants away from the vulnerable nasal cavity.



OPTIONS

- ❑ Alarm: Model 9001.5, 120 VAC emergency alarm and light system. Buzzer and flashing light are activated by a 1/2" IPS double pole, double throw flow switch.
- ❑ Tempered Water Blending Valves: Model 9201EFE Emergency Valve thermostatically mixes hot and cold water to provide a safe fluid supply for emergency eyewash equipment, with a flow rate of 12 gpm (45.4 L).
- ❑ Tempered Water Blending Systems: Model TWBS.EWE Lead-free Emergency Valve thermostatically mixes hot and cold water to provide a safe fluid supply for emergency eyewash equipment, with a flow rate of 12 gpm (45.4 L).

To see all options for this model, visit www.hawsc.com

SPECIFICATIONS

Model 7610 barrier-free sink/countertop eye/face wash shall include an AXION MSR™ eye/face wash head to help protect against the growth of mold and mildew on the treated components, and shall feature inverted directional laminar flow which achieves zero vertical velocity supplied by an integral flow control. Also included; polished chrome brass single action pull-down valve body, wheel chair accessibility, universal sign, and 1/2" O.D. (1.3 cm) slip joint inlet.

APPLICATIONS

Where safety is of the utmost importance and the eyes of any person may be exposed to injurious or corrosive materials, suitable facilities for quick flushing and cleansing of the eyes must be provided within the work area for immediate emergency use. When installed properly, the stable construction, counter top design of the 7610 is space efficient with its rear mounting location, and can accommodate barrier-free access.

Model is certified by CSA to meet the ANSI Z358.1 Standard for Emergency Eyewash and Shower Equipment.

