

TOTAL PROTECT

Anti-slip overshoe with safety cap

- Composition: Rubber and protective toe cap in aluminum/titanium
- Professional use: Prevents injuries in the work place: Slips and toe crushing
- ✓ **Aluminium/titanium toe cap : Ultra light!**
- ✓ **Outstanding grip coefficient**
- ✓ **Stretch fit structure : 4 Sizes to cover from 34 to 50**
- ✓ **Color code to track sizes**
- ✓ **Can be adapted to most kind of footwear**
- ✓ **Reusable - waterproof**
- ✓ **Tiger-grip® antislip sole with self cleaning studs**



REF « TP »

Certifications

EUROPEAN DIRECTIVE :
89/686/CE
(personal protective equipment)

 **EUROPEAN STANDARDS**

CE certification :
0075/1344/161/07/14/0618

- NF EN ISO 20345 / 2011
- NF EN 12568
- NF EN 13287
- Oil resistance (FO)

 **CE PPE CERTIFIED Risk II**

Certified organism:
CTC N° 0075/69367 Lyon - France

 **AMERICAN STANDARDS**

- ASTM F 2413-11
- ASTM F 2913

• NF EN 13287 – Antislip properties

Certification SRC = SRA + SRB

SRB : Anti-slip coefficient on steel floors with glycerin

SRA : Anti-slip coefficient on ceramic floors with detergent

Surface	Contact with	Standard ISO 13287	TOTAL PROTECT results
Steel	Oil	SRB = 0.18	+ 340% = 0.62
Ceramic	Detergent	SRA = 0.32	+140% = 0.54
	Water	-	0.62

Up to

• NF EN 12568 – Toe cap resistance :

200 joules resistance and resistant to crushing under max. Load of 1500 DaN

Physico-mechanical test

Test	Standard	TOTAL PROTECT results	Unit
Shock Resistance	EN ISO 20344	21.5	mm
Crushing resistance	EN ISO 20344	22	mm
Abrasion resistance	ISO 4649: 2002	159	mm ³
Density	ISO 4649: 2002	1.17	g/cm ³
FO resistance	EN ISO 20344	0.2	%
Tearing resistance	ISO 34-1 : 1994	11.6	daN/cm

Antistatisme: The overshoe meets antistatic and ESD properties.
The shoe and overshoe combination must necessarily be tested by the user

Sizes



	S				M				L				XL			
UE Sizes	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	+
UK Sizes	1.5	2.5	3.5	4.5	5.5	6	6.7	7.5	8	9	9.5	10.25	11	11.8	13	+
US Woman	4	5	6	7	7.5	8	8.5	9	9.5	10	11					
US Man					5.5	6.25	7	7.75	8.5	9.5	10	10.75	11.5	12.3	13	+

For a proper use of the overshoes, it is important to ensure that the overshoes fit neatly over the user's footwear

Storage and maintenance




- Hand washable - Let them dry naturally
- Store in a dry place, away from temperature variation
- Do not use below a temperature of -20°C.

Design and manufacturing: TIGER-GRIP ENGINEERING

 contact@tigergrip.com

 120, rue Fournier
31700 BEAUZELLE, France

 + 33 5 34 60 56 56

www.tigergrip.com