



## INAP-Profiler

safety helmet according to EN 397

- Application field**
  - construction zones
  - industrial firms
  - cold zones of construction and industry where the use of safety helmets is required
- Shell**
  - manufactured from Polyethylene (PE)
  - innovative form with shell slightly drawn down at the neck
  - lateral slots for ear defenders (30 mm)
  - adjustable holes for effective ventilation
- Harness**
  - 4- or 6-point webbed harness with chin strap fastenings
  - angled neckband
  - exchangeable highly absorbent sweatband
  - foam cushions band
- Additional testing**
  - temperatures down to -20° C
- Durability**
  - up to 5 years
- Size adjustment**
  - I - III / from 51-64 cm in steps of 0,5 cm
- Weight of shell**
  - approx. 210 g
- Packing details**
  - up to 30 helmets per model or colour in one box
- Individualization**
  - application of logos by silk screen method (up to four colours) or self-adhesive foil (up to six colours), reflective stripes, material dyeing in special colour, fluorescent colour
- Size of logos**
  - front: approx. 60 x 40 mm / side: approx. 80 x 20 mm
- Accessories/Spare parts**
  - face protection, ear defenders, VOSS-Lock ratchet, chin straps

### Colours

Item number

#### Sulfur-yellow / RAL1016

4-Pnt-web. Harn. 11051016  
6-Pnt-web. Harn. 11101016

#### Traffic orange / RAL2009

4-Pnt-web. Harn. 11052009  
6-Pnt-web. Harn. 11102009

#### Carmine red / RAL3002

4-Pnt-web. Harn. 11053002  
6-Pnt-web. Harn. 11103002

#### Signal white / RAL9003

4-Pnt-web. Harn. 11059003  
6-Pnt-web. Harn. 11109003

#### Mint green / RAL6029

4-Pnt-web. Harn. 11056029  
6-Pnt-web. Harn. 11106029

#### Signal blue / RAL5005

4-Pnt-web. Harn. 11055005  
6-Pnt-web. Harn. 11105005