

Technical Datasheet

E-A-R™ Express™ Earplugs

Corded EX-01-001
Uncorded EX-01-002



Product Description

The E-A-R™ Express™ pod earplugs are designed for insertion into the ear canal to help reduce exposure to hazardous levels of noise and loud sound. This product is available in corded and uncorded versions.

Key Features

- Unique pod design
- Foam tip which is shaped and sized to mould comfortably thus providing an effective seal
- No roll-down required
- Insertion stem helps eliminate the need to touch the tip when fitting
- One size fits the majority of wearers
- Washable and reusable
- Supplied in a re-sealable pillow-pack for ease of use
- Available in both corded and uncorded versions

Applications

The E-A-R™ Express™ earplugs are ideal for moderate to high noise exposure levels, and are ideally suited for all frequency noise in a wide range of industrial workplaces and leisure environments.

Examples of typical applications include:

- Automotive
- Construction
- Chemical & pharmaceutical manufacture
- Heavy engineering
- Metal processing
- Textile manufacture
- Woodworking

Standard & Approval

The E-A-R™ Express™ pod earplugs have been tested and CE approved against the European Standard EN352- 2:1993. These products meet the Basic Safety Requirements as laid out in Annex II of the European Community Directive 89/686/EEC and have been examined at the design stage by INSPEC International Limited, 56 Leslie Hough Way, Salford, Greater Manchester M6 6AJ, UK (Notified Body number 0194).

Materials

The following materials are used in the manufacture of this product.

Component	Material
Earplugs	Polyurethane Foam
Cord	PVC



Attenuation values

Frequency (Hz)	63	125	250	500	1000	2000	4000	8000
Mf (dB)	27.8	26.0	24.9	25.2	29.4	34.9	37.0	35.9
sf (dB)	5.4	4.5	3.3	5.0	4.2	4.1	5.2	3.7
APVf (dB)	22.4	21.5	21.5	20.2	25.2	30.8	31.8	32.2

SNR = 28dB H = 30dB M = 24dB L = 22dB

Key

APVf (dB) = Mf – sf (dB)

Mf = Mean attenuation value

sf = Standard deviation

APVf = Assumed Protection Value

H = High-frequency attenuation value (predicted noise level reduction for noise with L(C) – L(A) = -2dB)

M = Medium-frequency attenuation value (predicted noise level reduction for noise with L(C) – L(A) = +2dB)

L = Low-frequency attenuation value (predicted noise level reduction for noise with L(C) – L(A) = +10dB)

SNR = Single Number Rating (the value that is subtracted from the measured C-weighted sound pressure level, L(C) in order to estimate the effective A-weighted sound pressure level inside the ear).

Important Notice

3M does not accept liability of any kind, be it direct or consequential (including, but not limited to, loss of profits, business and/or goodwill) arising from reliance upon any information herein provided by 3M. The user is responsible for determining the suitability of the products for their intended use. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.



Occupational Health Group
3M United Kingdom plc
3M Centre
Cain Road, Bracknell
Berkshire, RG12 8HT
Tel: 0870 60 800 60
www.3M.co.uk/ohes

Occupational Health Group
3M Ireland Limited
The Iveagh Building
The Park, Carrickmines
Dublin 18
Tel: 1 800 320 500