

# Dextram 375

## DESCRIPTION AND GENERAL PROPERTIES

- **Material** Nitrile
- **Length (cm)** 26
- **Wrist** Scalloped cuff
- **Colour/Color** Yellow
- **Interior finish** Textile support
- **Exterior finish** Smooth
- **Size / EAN** 6 7 8 9
- **Packaging** 1 pair/bag - 5 pairs/box - 50 pairs/carton
- **Complementary information** Guaranteed without silicone



## PERFORMANCE RESULTS

Certification category 2



3111

### Legends



**MECHANICAL  
HAZARDS  
EN 388**

PERFORMANCE LEVELS

0-4 0-5 0-4 0-4  
 └─ Blade cut resistance  
 └─ Abrasion resistance  
 └─ Tear resistance  
 └─ Puncture resistance



**LOW CHEMICAL  
PROTECTION  
EN 374**



**MICRO-ORGANISMS  
EN 374**



**RADIOACTIVE  
CONTAMINATION  
EN 421**



**HEAT  
AND FIRE  
EN 407**

PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4  
 └─ Burning behaviour  
 └─ Contact heat resistance  
 └─ Convective heat resistance  
 └─ Radiant heat resistant  
 └─ Resistance to small drops of molten metal  
 └─ Resistance to large quantities of molten metal



**SPECIFIC CHEMICAL  
PROTECTION  
EN 374**

Letter Code	Chemical product
A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofuran
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



**COLD HAZARDS  
EN 511**

PERFORMANCE LEVELS

0-4 0-4 0 or 1  
 └─ Convective cold resistance  
 └─ Contact cold resistance  
 └─ Water permeability

For more details: [www.mapa-pro.com](http://www.mapa-pro.com)

## DESCRIPTION AND GENERAL PROPERTIES

- Exceptionally comfortable lining: no seams on the working surfaces
- Good abrasion resistance
- Protection against humidity, oil and grease splashes

## MAIN FIELDS OF USE

### Automotive/mechanical industry

- Precision mechanical work
- Handling oily mechanical parts

### Construction Industry (Painters/Decorators)

- Applying finishes
- Preparing surfaces

### Other industries

- Wood working
- Sanding
- Packaging
- Manufacturing small electrical components

## INSTRUCTIONS FOR USE

### Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the « CE »-type test.
- Put the gloves on dry, clean hands.
- It is not recommended for persons sensitized to dithiocarbamates and thiazoles to use these gloves.
- Rub over the gloves stained with oil or grease using a dry cloth before taking them off.
- Inspect the gloves for snags or tears before reusing them.

### Storage conditions

Store the gloves in their original packaging protected from direct light and heat sources.

### Laundering conditions

Caution: using the gloves or submitting them to another cleaning or laundering process can alter their performance levels.

### Drying conditions

Ensure the inside of the gloves is dry before putting them on again.

## LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- CE-Type Examination Certificate

0072/014/162/12/96/0681

- Issued by the notified body nr

0072

I.F.T.H. – Av. Guy de Collongue - F-69134 ECULLY CEDEX